













# Simple. Powerful. Portable.

Smaller and lighter than a mobile phone, the 1600 series can be easily fit in your pocket and carried around for required tasks wherever it takes. The 1600 series is built to meet the needs in healthcare, field sales and field service with strong mobility requirement. Optional *Bluetooth*® connectivity allows instant data acquisition to a *Bluetooth*® compatible PDA, laptop, PC or any other *Bluetooth*®-enabled devices. With a choice of linear imager, laser or 2D imager, your business needs will be met in a wide range of applications.



#### **Maximum Mobility and Durability in Pocket-size**

The 1600 series liberates and mobilizes healthcare and field workers with its ultra-portable, light-weight form factor combined with optional <code>Bluetooth®</code> connectivity. Mobile salespeople or field service technicians could combine the 1600 series with a PDA or Smartphone to collect and transmit data via WWAN, ensuring the back-end system is always up-to-date. Furthermore, the pocket-sized IP42 certified device passed the 1.5 m drop test which allows workers to roam freely about their workspaces without worries.



#### **Versatile Symbology Support**

With optional linear imager, laser and 2D imager, the 1600 series can sufficiently retrieve 1D barcode data up to 3 mil resolution. Additionally, the 1600 series ensures hospitals, pharmacies, clinics and laboratories are ready to meet the growing adoption of 2D barcodes on the product packaging. CipherLab 1600 series is also ideal for scanning patient identification bracelets and medication labels. It frees healthcare professionals from paperwork, allowing them to provide higher-quality care to patients.



### **Smart Solution with Immediate Payoffs**

#### Simplifying and streamlining with CipherLab 1600 series scanners

Hong Kong's historic Tung Wah Hospital adopts CipherLab 1600 series scanners to more efficiently deal with fixed assets. After expanding to nearly 700 beds, it was clear to Tung Wah Hospital administration that they needed an efficient way to inventory fixed assets. With the decision to deploy CipherLab 1600 series *Bluetooth*® scanners paired with laptops and PCs, the hospital has seen an enormous reduction in labor and cost associated with asset management.

## **Optimum Storage Capacity and Reliable Data Transmission**

The 1600 series can hold over 240,000 scans\* in batch mode when used as a memory scanner, allowing workers to complete the maximum number of tasks without interruption. Besides, the scanners also have buffer memory up to 10 KB for up to 600 scans\* ensuring no data is lost if a worker is out of *Bluetooth*® working range. Once the worker is back in range, information is automatically uploaded to the back-end system.

\*The calculation is based on EAN13 barcode

#### **Long Lasting Performance, Optimal Productivity**

The 1600 series allows employees optimal productivity by providing long working hours for all-day data collection on either replaceable AAA batteries, or rechargeable Li-ion batteries. The less the time is wasted on frequent recharging, the more the human resource can be released to serve more patients.

#### Instant Pairing via Bluetooth®

Paired with the CipherLab 3610 *Bluetooth*® transponder, the 1600 series allows real-time data transmission to laptop, computer, or tablet. Having an extended *Bluetooth*® working range of up to 20 meters gives users more flexibility, caregivers, for example, can scan patients' wristbands without pushing around a medical cart.

#### **Time Stamp – Keeping Track for Data Analysis**

Time Stamp is an excellent tracking function that associates all of the barcode reads with the exact date and time. Its accurate time keeping makes efficient data analysis effortless. You can now evaluate the time that a worker is needed to finish a round of data collection. (For 1662 / 1663 / 1664)

# wara Support

## **Higher Flexibility with Extensive Software Support**

ScanMaster -

Custom Configure Scanners at No Additional Cost

The ScanMaster software offers a comprehensive solution to configure scanners, edit format and symbol types, and much more. It's easy to use and set up through the standard Windows® interface. All generated settings can be saved and printed out as barcodes to share with other users, so other users can scan to configure their scanners.

CipherConnect – Work Smarter Utilizing PDAs and Smartphones

CipherConnect is a COM-to-key software utility designed for CipherLab cordless scanners to work as an input device for smart devices – enabling intensive data collection via *Bluetooth*® Serial Port Connection. Now it is available for Android, Blackberry, and Windows® Mobile via *Bluetooth*® SPP (Slave),\*

\*Apple's iPhone, and iPod Touch (2nd Generation) support *Bluetooth*® HID profiles when running iOS 4 and above, where CipherConnect isn't needed to











ket-si		

		1662	1663	1664		
RF	Module	Bluetootth® Class 2 (2.4 GHz) Version 2.1 +EDR				
Communication	Coverage	20 m / 66 ft. line of sight				
	Standard profile	SPP, HID				
Performance	Category	<i>Bluetooth</i> <sup>®</sup> laser scanner	Bluetooth® linear imager scanner	Bluetooth® 2D imager scanner		
	Optical sensor	Laser	2500 pixels	1280 x 960 pixels		
	Light source	Visible laser diode at 650 nm	625 ±5 nm Red LEDs (2x)	White LED (1x)		
	Resolution	4 mil	3 mil	3 mil - 1D barcode / 5 mil - 2D barcode		
	Depth of field (depends on barcode resolution)	2 to 42 cm / 0.8 to 16.5 in.	2.4 to 38 cm / 0.9 to 15 in.	Code 39 3 mil: 7 to 17 cm / 2.7 to 6.6 in. Code 39 5 mil: 6 to 22 cm / 2.3 to 8.6 in. UPCA 100%: 5 to 45 cm / 1.9 to 17.7 in. PDF417 5mil: 7 to 13 cm / 2.8 to 5.1 in. PDF417 7 mil: 6.5 to 18 cm / 2.5 to 7 in. Data Matrix 10 mil: 4 to 20 cm / 1.5 to 7.8 in. QR Code 15 mil: 6 to 28 cm / 2.3 to 11 in. QR Code 20 mil: 5 to 35 cm / 1.9 to 13.7 in.		
	Scanning angle	Pitch ± 65°, Skew ± 50°	Pitch ±70°, Skew ±70°	Pitch ± 60°, Skew ± 60°		
	PCS	Minimum 30%		Minimum 20%		
	Scan rate	100 scans / second	200 scans / second	30 scans / second		
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar(RSS), Industrial 2 of 5, Interleaved 2 of 5, Code 32 (Italian Pharmacode), Trioptic Code 39, MSI, ISBT-128, Bookland EAN, UPC/EAN/GS1-128	Codabar, Code 39, Code 93, Code 128, GS1 DataBar(RSS), Industrial 2 of 5, Interleaved 2 of 5, Code 32 (Italian Pharmacode), French Pharmacode, Matrix 2 of 5, MSI, Plessey, ISBT-128, Telepen, UPC/EAN/GS1-128, and more	1D: All major codes¹ 2D: PDF417, MicroPDF417, Data Matrix, QR code, Micro QR Code, Aztec, MaxiCode, Han Xin Code, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)		
	Programmable features	Data editing, interface selection, symbology configuration				
	Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Swiss German, Japanese, Turkish, Hungarian, and Danish				
Physical	Weight (including battery)	100 g / 3.53 oz	106 g / 3.7 oz.	98.7 g / 3.48 oz.		
	Size LxWxH	11.3 x 4.5 x 3.0 cm / 4.4 x 1.8 x 1.2 in.				
	Color	Black				
	Button	Power and scan keys				
	Memory	4 MB				
Electrical	Working hours	35 hours based on 1 scan / 5 seconds	40 hours based on 1 scan / 5 seconds	24 hours based on 1 scan / 5 seconds		
	Power Supply	Li-ion 3.7V, 850 mAh				
	Power consumption Standby / Operating	20 mA / 100 mA @3.7 V	20 mA / 224 mA @3.7V	25 mA / 270mA @3.7V		
User Environment	Temperature	Operating : 0 °C to 50°C / 32°F to 122°F, Storage : -20°C to 60°C / -4°F to 140°F( w/o battery )				
	Humidity (non-condensing)	Operating : 10% to 90% / Storage: 5% to 95%				
	Impact resistance	1.5 m / 4.9 ft. multiple drops onto concrete				
	Ingress protection	IP42				
	Electrostatic discharge					
	EMC regulation	BSMI, CE, RCM, FCC, NCC, IC, JRL	BSMI, CE, RCM, FCC,IC, NCC	BSMI, CE, RCM, FCC, NCC, IC, JRL		
Configuration		Setup option includes Windows®- based ScanMaster software				
Accessories		3610 Bluetooth® transponder, Micro USB cable, battery charger, protective cover				
Warranty		1 year				

1. All of the barcodes that 1664 2D scanner can read except French Pharmacode, Plessey, and Telepen.





3610 Bluetooth® Transponder



**Battery Charger** 



**Protective Cover** 



**HEADQUARTERS** CipherLab Co., Ltd. 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669 Tel +886 2 8647 1166 Fax +886 2 8732 3300 www.cipherlab.com

CipherLab Electronics Trading (Shanghai) Co., Ltd. E Room, 9F, No.726 West Yan'an Rd. Changning District, Shanghai China 200050 Tel +86 21 3368 0288 Toll Free 400 920 0285

Fax +86 21 3368 0286

CipherLab USA Inc. 2552 Summit Avenue STE 400 Plano, Texas USA 75074 Tel +1 469 241 9779 Toll Free 888 300 9779 Fax +1 469 241 0697

CipherLab Europe Cahorslaan 24, 5627 BX Eindhoven, The Netherlands Tel +31 (0) 40 2990202